

## EXTRA 5W-30

### HIGH-PERFORMANCE MOTOR OIL



#### DESCRIPTION AND APPLICATION

EXTRA 5W-30 is a high-performance synthetic technology motor oil designed for use in both gasoline and diesel engine vehicles.

#### FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against engine wear even under the most demanding operating conditions.
- Its high oxidation stability extends oil change intervals and preserves product performance.
- Outstanding fluidity at low temperatures ensures easy cold starts and rapid oil circulation in the engine during winter.
- Suitable for use in diesel and gasoline passenger cars as well as light commercial vehicles.
- Compatible with Diesel Particulate Filters (DPF) and all gasoline catalytic converters.
- Delivers long-lasting engine protection against wear, sludge, and deposits with excellent performance at both low and high temperatures.

#### PERFORMANCE

SAE 5W-30, API SN/CF, ACEA A3/B4-08-12, MB 229.5, VW-norm 502 00/505 00, BMW Longlife-01, PORSCHE A40, RENAULT RN 0700/0710, OPEL GM-LL-B-025, TOYOTA, NISSAN, HONDA, MITSUBISHI, MAZDA, SUBARU, ISUZU, DAIHATSU, SUZUKI, KIA, HYUNDAI

#### HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub engine oil should not come into contact with skin. Do not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Korelub engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material

#### STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

#### TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	EXTRA 5W-30
Density, g/cm <sup>3</sup> 15°C	ASTM D 4052	0,860
Kinematic Viscosity cSt, 100°C	ASTM D 445	9,3-12,6
Viscosity Index min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-35
Flash Point, °C, min	ASTM D 92	200

#### PACKAGING TYPES

