

EXTRA 5W-40

HIGH-PERFORMANCE SYNTHETIC MOTOR OILS



DESCRIPTION AND APPLICATION

It is a high-performance motor oil with synthetic technology, offering superior cleaning and protection properties. Provides excellent cold start performance and high-temperature protection. Thanks to its engine cleaning and wear prevention features, it offers extended oil change intervals.

FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against potential engine wear even under the most demanding operating conditions.
- Its enhanced friction-reducing properties contribute to improved fuel economy.
- High oxidation stability helps maintain oil performance until the next oil change.
- Low volatility reduces oil consumption.

PERFORMANCE

SAE 5W-40, API SN/CF, ACEA A3/B4-08-12, MB 229.5, VW-norm 502 00/505 00, BMW Longlife-01, PORSCHE A40, RENAULT RN 0700/0710, OPEL GM-LL-B-025, TOYOTA, NISSAN, HONDA, MITSUBISHI, MAZDA, SUBARU, ISUZU, DAIHATSU, SUZUKI, KIA, HYUNDAI.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub motor oil should not come into contact with skin or eyes, should not be ingested, and its vapors should not be inhaled. If it comes into contact with skin or eyes, the affected area should be washed thoroughly with soap and water, and medical assistance should be sought if necessary. In case of ingestion, do not induce vomiting and seek immediate medical attention. If vapors are inhaled, ensure exposure to fresh air and seek medical help if required. Used Korelub motor oil should be collected in appropriate waste oil collection containers and delivered to authorized recycling centers in compliance with the applicable waste management regulations. It should not be disposed of in trash, sewage, or nature, and should not be mixed with any other petroleum product or chemical. Containers should not be thrown away or left in the environment but delivered to licensed recycling facilities. The product must not be burned.

STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	EXTRA 5W-40
Density, g/cm ³ 15°C'	ASTM D 4052	0,850
Kinematic Viscosity cSt, 100°C'	ASTM D 445	12,5-16,3
Viscosity Index min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-39
Flash Point, °C, min	ASTM D 92	235

PACKAGING TYPES

