



PREMIUME 0W-20

HIGH-PERFORMANCE OILS



DESCRIPTION AND APPLICATION

PREMIUME 0W-20 is a fully synthetic motor oil produced with state-of-the-art additives for modern passenger car engines.

FEATURES AND BENEFITS

- Thanks to its synthetic formulation, it provides unique protection and fuel economy
- It extends engine life and lubrication intervals.
- Delivers full performance under all climate and road conditions.
- Eliminates all wear that may occur during engine start-up.

PERFORMANCE

SAE 0W-20, API SP, ILSAC GF-6A, GM dexos1, CHRYSLER MS-6395, TOYOTA, NISSAN, HONDA, MITSUBISHI, MAZDA, SUBARU, ISUZU, DAIHATSU, SUZUKI, KIA, HYUNDAI

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Korelub engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material

STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	PREMIUME 0W-20
Density, g/cm ³ 15°C'	ASTM D 4052	0,855
Kinematic Viscosity cSt, 100°C'	ASTM D 445	8-9
Viscosity Index min.	ASTM D 2270	150
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min	ASTM D 92	225

PACKAGING TYPES

