


PRIME DPF 5W-30

HIGH-PERFORMANCE SYNTHETIC ENGINE OILS



DESCRIPTION AND APPLICATION

This advanced synthetic engine oil, developed with LOW SAPS technology, is specially designed to meet the requirements of vehicles equipped with new-generation DPF systems. PRIME DPF 5W-30 is recommended for high-performance gasoline and diesel engines, especially for modern passenger cars, SUVs, and light commercial vehicles.

FEATURES AND BENEFITS

- Provides excellent protection against engine wear, even under the most challenging operating conditions, thanks to its new additive technology.
- Offers superior cleaning capabilities to keep the engine in optimal condition.
- Enhances fuel economy with advanced friction-reducing properties.
- Maintains its performance characteristics until the next oil change due to high oxidation stability.
- Reduces oil consumption with its low volatility.
- Delivers extra performance compared to conventional motor oils.
- Provides excellent performance in DPF-equipped vehicles with its low ash content.

PERFORMANCE

SAE 5W-30, API SN/CF, ACEA C3, MB 229.31/229.51/229.52, BMW Longlife-04, VW-norm 502 00/505 00/505 01, OPEL GM Dexos2, FORD WSS-M2C 917-A, FIAT 9.55535-S2, RENAULT RN 0720, TOYOTA, NISSAN, HONDA, MITSUBISHI, MAZDA, SUBARU, ISUZU, DAIHATSU, SUZUKI, KIA, HYUNDAI

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Korelub engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material

STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	PRIME 5W-30
Density, g/cm ³ 15°C'	ASTM D 4052	0,850
Kinematic Viscosity cSt, 100°C'	ASTM D 445	9,3-12,6
Viscosity Index min.	ASTM D 2270	165
Pour Point, °C, max.	ASTM D 97	-42
Flash Point, °C, min	ASTM D 92	230

PACKAGING TYPES

