



PRIME DPF 5W-40

HIGH-PERFORMANCE DPF OILS



DESCRIPTION AND APPLICATION

Produced with synthetic LOW SAPS technology, this advanced motor oil is designed to meet the requirements of new-generation vehicles equipped with DPF systems. PRIME DPF 5W-40 is recommended for all types of modern vehicle engines, particularly high-performance gasoline and diesel engines in the latest passenger cars, SUVs, and light commercial vehicles.

FEATURES AND BENEFITS

- Thanks to its new additive technology, it provides excellent protection against wear that may occur in the engine even under the toughest operating conditions
- With its improved anti-friction properties, it ensures fuel economy.
- Its high oxidation stability allows it to maintain its properties until the next oil change.
- With low volatility, it reduces oil consumption.
- Delivers extra performance compared to conventional motor oils.
- With its low ash content, it provides excellent performance in vehicles with DPF systems.

PERFORMANCE

SAE 5W-40, API SN/CF, ACEA A3/B4-08-12, MB 229.5, VW-norm 502 00/505 00, BMW Longlife-04, PORSCHE A40, RENAULT RN 0700/0710, OPEL GM-LL-B-025, TOYOTA, NISSAN, HONDA, MITSUBISHI, MAZDA, SUBARU, ISUZU, DAIHATSU, SUZUKI, KIA, HYUNDAI.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Korelub engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material

STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	PRIME 5W-40
Density, g/cm ³ 15°C'	ASTM D 4052	0,855
Kinematic Viscosity cSt, 100°C'	ASTM D 445	12,5-16,3
Viscosity Index min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-40
Flash Point, °C, min	ASTM D 92	240

PACKAGING TYPES

