

TOP-END 10W-40

SYNTHETIC HIGH-PERFORMANCE ENGINE OIL



DESCRIPTION AND APPLICATION

This motor oil is specially developed with synthetic technology to provide effective lubrication and protection. It is a synthetic engine oil designed for four-stroke gasoline, LPG, and diesel engines (non-DPF equipped), meeting the API SN/CF and ACEA A3/B4 specifications. It can be safely used in passenger cars and vans with turbocharged, direct injection, or non-injection engines year-round.

FEATURES AND BENEFITS

- Maintains its durable film strength and protection even under challenging operating conditions.
- Active cleaning properties control soot and sludge buildup, keeping the engine clean.
- High oxidation stability preserves its properties until the next oil change.
- Provides excellent protection against rust and wear with its special additive composition.
- High viscosity index ensures smooth engine operation in all seasons.

PERFORMANCE

SAE 10W-40, API SN/CF, ACEA A3/B4, MB 229.3, BMW Longlife-04, VW 502 00/505 00, RENAULT RN 0700/0710, FIAT 9.55535-S2, GM LL-A/-B-025.

HEALTH, SAFETY, AND ENVIRONMENTAL RECOMMENDATIONS

Korelub engine oil should not come into contact with skin or eyes, should not be swallowed, and its vapors should not be inhaled. In case of contact with skin or eyes, rinse thoroughly with soap and water and seek medical attention if necessary. If swallowed, do not induce vomiting and seek emergency medical attention. If vapors are inhaled, take deep breaths and seek medical help if needed. Used Korelub engine oils must not be discharged into drains, sewers, or the environment. They should be collected in designated waste oil containers and delivered to authorized recycling centers in accordance with the applicable regulations. They must not be mixed with other petroleum derivatives or chemicals and should not be burned in stoves or furnaces. Empty containers should not be disposed of in landfills or the environment but handed over to licensed recycling organizations. For detailed information, you can review the "Material

STORAGE CONDITIONS

Korelub engine oil packages should not be exposed to direct sunlight for extended periods. Packages must not come into contact with water. Oils should not come into contact with dust and should be kept away from dusty environments. The ambient temperature should not exceed 40°C. The proper use of this product in compliance with current laws and regulations is the sole responsibility of the user. Korelub cannot be held liable for any damages or adverse effects resulting from improper use or deviations from the intended purpose or the product's inherent hazards.

TYPICAL PROPERTIES

PHYSICAL PROPERTIES	METHOD	TOP-END 10W-40
Density, g/cm ³ 15°C'	ASTM D 4052	0,850
Kinematic Viscosity cSt, 100°C'	ASTM D 445	12,5-16,3
Viscosity Index min.	ASTM D 2270	160
Pour Point, °C, max.	ASTM D 97	-39
Flash Point, °C, min	ASTM D 92	235

PACKAGING TYPES

